


Atenic GmbH
Lauchwasenstraße 1
76709 Kronau
Tel: +497253 845 423 4
Email: info@atenic.com



ATENIC all rights reserved
Designs and specifications may change without prior notice.

ATENIC
Outdoor Lighting




FP06MINI flexible wall washer
IP rating: IP67
Input Voltage:24V DC
Power:15W/m
Maximum 5 meters
Beam angle:25°/45°/15° X 55°
Application: suit for commercial lighting,
wall washing illumination
Installation:surface mounting
Working Temperature:-40°C~+45°C

suit for class 2 power unit,
maximum connected power not more than 100W





FP06-27 flexible wall washer
IP rating: IP67
Input Voltage:24V DC
Power:30W/m
Maximum 3 meters
Beam angle: 15°/20°/20° X 40°/20° X 50°
Application: suit for commercial lighting,
wall washing illumination
Installation: surface mounting
Working Temperature:-40°C~+45

suit for class 2 power unit, maximum connected power not more than 100W




3D Flex Grazer




3D Flex Grazer

IP67 high power 3D flex LED grazer has been designed with anti-glare housing, flexible, easy to fix, 24V DC, power up to 45W in 1200mm length, Beam angle 15°/20°/20°×40°/20°×50° are available, it is an ideal product for indoor and outdoor architectural lighting project

suit for class 2 power unit, maximum connected power not more than 100W








FP06SB IP67 Flexible Wall Washer



Part No.	Description
1.01.07.0123	Stainless steel mounting clip
1.01.05.0030 (M3*16mm)	Self-tapping screws

Sealed with fully transparent and waterproof materials, soft and bendable
IP rating: IP67
Beam angle: 20 °/30°/40 °/55°/20°X36°
Maximum 5 meters
Application: suit for commercial lighting , wall washing illumination
Installation: surface mounting
Maximum: 19.2W/m
Length: 5000mm/reel
max interconnected wattage is 100W.
suit for class 2 power unit,
maximum connected power not more than 100W




FP06 IP67 Flexible Wall Washer




Optic flexible wall washer LED stirp - IP67
Input Voltage:24V DC
Power:19.2W/m(Symmetric),16W/m(Asymmetric)
Single CCT: 2500K/ 2700K/3000K/3500K/4000K/6500K;
Tunable white CCT:2700K-6500K;
DMX control:
1.DMX single CCT 2500K/ 2700K/3000K/3500K/4000K/6500K;
2.DMX Tunable white CCT 2700K-6500K;
3.DMX RGB;
Beam angle: 20°/30°/40°/50°/25° X 40°,110° x 70°(Asymmetric)
Cutttable
Maximum 5 meters
Application: suit for commercial lighting,
wall washing illumination
Working Temperature:-40°C~+45°C
For outdoor application, must be used together with aluminum
housing for heat release.


suit for class 2 power unit, maximum connected power not more than 100W




Part No.	Description	Picture	Part No.	Description	Picture
1.05.025.0225 (1.046m) 1.05.025.0224 (2.046m) 1.05.025.0227 (3.16m)	Aluminum profile		2.03.LL.0002	2 PIN Female Connection Cable	
1.01.04.25.0004 1.01.05.0277 (M2.6*8mm)	End cap- E1 Self-tapping screws		2.03.LL.0001	2 PIN Male Connection Cable	
1.01.04.25.0005 1.01.05.0277 (M2.6*8mm)	End cap- E2 Self-tapping screws		2.03.LL.0010	2 PIN Female Connection Cable from Left Side	
1.04.02.25.0014 (1.046m) 1.04.02.25.0013 (2.046m) 1.04.02.25.0017 (3.16m)	PC37-30 PC COVER -P1		2.03.LL.0009	2 PIN Male Connection Cable from Right Side	
1.04.02.25.0007 (3.02m)	FP06-30 PC COVER -P2		2.03.LL.0003	2 PIN join connector	
1.01.07.0091 1.01.05.0030 (M3*16mm)	Stainless steel mounting clip Self-tapping screws		2.03.LL.0012	End cap	
1.01.07.0101 1.01.05.0296 (M3*16mm) 1.01.05.0218 (M3*3mm)	90 degree turnable clip Self-tapping screws		1.11.01.0098	UV glue	
1.13.13.0247	UV light				



20°(Symmetric)






25° X 40°(Symmetric)



110° x 70°(Asymmetric)



Part No.	Description	Picture	Part No.	Description	Picture
1.05.035.0123 (1.2m)	Aluminum profile		1.05.035.0124 (1.2m)	Aluminum fixing holder	
			1.01.05.0030 (M3*16mm)	Self-tapping screws	
	PC hyaline surface			End cap	
1.01.06.0033	Rope system for hang up, 1.5 meter length (for hang up application)		1.09.03.0227	LED power supply Led Power supply to be purchased separately	




Dimension: L1200*W35*H80mm
(Customized length is available on request.)
Input voltage:30-36V DC/900mA(MAX)
Power: 30W
Beam Angle:15°/20°/18°× 45°/18°× 55°
Color Temperature: 2700-6500K
CRI:≥90
Working Temperature:-40°C~+45°C
three in one dimming function
(0/1-10V DC or PWM signal or resistance)
Led Power supply to be purchased separately




WP02AL1 (AP0501AL1) IP67 LED Linear Light



Part No.	Description	Picture	Part No.	Description	Picture
1.05.005.0014 (1m) 1.05.005.0015 (2m) 1.05.005.0016 (3m)	Aluminum profile		1.02.04.05.0014 (with hole) 1.02.04.05.0015 (w/o hole)	End cap PC white	
1.16.005.0040 (1m) 1.16.005.0041 (2m) 1.16.005.0042 (3m)	PMMA one time extrusion profile		1.05.005.0040 1m 1.05.005.0041 2m 1.05.005.0042 3m	Aluminum plate	
			1.11.01.0079	EPOXY ADHESIVE	

IP67 LED Profile
Dimension: W20.2*H16.2*L1000mm
(Customized length is available on request.)
Input voltage:24V DC
Power: 10W/meter
120pcs LED per meter
Color Temperature: 2400-6500K
CRI:≥80
(CRI more than 80 is available on request)
Beam Angle: 110°
Cable length: 200mm
(Option : Cable comes from the side,from the end,from the bottom)
IP rating: IP67
Working Temperature:-40°C~+45°C
Fire rating:HB

Application: suit for indoor or outdoor light decoration
suit for class 2 power unit, maximum connected power not more than 100W



WP02AL3 (AP0501AL3) IP67 LED Linear Light





Part No.	Description	Picture	Part No.	Description	Picture
1.05.005.0206 (1m) 1.05.005.0207 (2m) 1.05.005.0208 (3m)	Aluminum profile		1.02.04.05.0014 (with hole) 1.02.04.05.0015 (w/o hole)	End cap PC white	
1.16.005.0040 (1m) 1.16.005.0041 (2m) 1.16.005.0042 (3m)	PMMA one time extrusion profile		1.01.04.05.0001 1.01.05.0356 (M2.6*10)	End cap Self-tapping screws	
			1.05.005.0040 1m 1.05.005.0041 2m 1.05.005.0042 3m	Aluminum plate	

1.11.01.0079 EPOXY ADHESIVE



IP67 LED Profile
Dimension: W36.4*H35*L1000mm
(Customized length is available on request.)
Input voltage:24V DC
Power: 10W/meter
120pcs LED per meter
Color Temperature: 2400-6500K
CRI:≥80
(CRI more than 80 is available on request)
Beam Angle: 110°
Cable length: 200mm
(Option : Cable comes from the side,from the end,from the bottom)
IP rating: IP67
Working Temperature:-40°C~+45°C
Fire rating:HB

Application: suit for indoor or outdoor light decoration
suit for class 2 power unit, maximum connected power not more than 100W



WP02AL4 (AP0501AL4) IP67 LED Linear Light





Part No.	Description	Picture	Part No.	Description	Picture
1.05.005.0280 (1m) 1.05.005.0281 (2m) 1.05.005.0282 (3m)	Aluminum profile		1.05.005.0040 1m 1.05.005.0041 2m 1.05.005.0042 3m	Aluminum plate	
1.16.005.0040 (1m) 1.16.005.0041 (2m) 1.16.005.0042 (3m)	PMMA one time extrusion profile		1.11.01.0079	EPOXY ADHESIVE	
1.02.04.05.0014 (with hole) 1.02.04.05.0015 (w/o hole)	End cap PC white		1.01.04.05.0015	End cap	
			1.01.05.0356 (M2.6*10)	Self-tapping screws	

IP67 LED Profile
Dimension: W20.4*H29.8*L1000mm
(Customized length is available on request.)
Input voltage:24V DC
Power: 10W/meter
120pcs LED per meter
Color Temperature: 2400-6500K
CRI:≥80
(CRI more than 80 is available on request)
Beam Angle: 110°
Cable length: 200mm
(Option : Cable comes from the side,from the end,from the bottom)
IP rating: IP67
Working Temperature:-40℃~+45℃
Fire rating:HB

Application: suit for indoor or outdoor light decoration

suit for class 2 power unit, maximum connected power not more than 100W



WP03AL1 (AP0502AL1) IP67/IP68 LED Linear Light




Part No.	Description	Picture	Part No.	Description	Picture
1.05.015.0014 (1m) 1.05.015.0015 (2m) 1.05.015.0016 (3m)	Aluminum profile		1.02.04.15.0019 (with hole) 1.02.04.15.0020 (w/o hole)	Frosted end cap	
1.16.005.0056 (1m) 1.16.005.0057 (2m) 1.16.005.0058 (3m)	PMMA one time extrusion profile		1.05.015.0034 1m 1.05.015.0036 2m 1.05.015.0037 3m	Aluminum plate	
			1.11.01.0079	EPOXY ADHESIVE	

IP67/IP68 LED Profile
Dimension: W24.7*H20.7*L1000mm
(Customized length is available on request.)
Input voltage:24V DC
Power: 15W/meter
120pcs LED per meter
Color Temperature: 2400-6500K
CRI:≥80
(CRI more than 80 is available on request)
Beam Angle: 110°
Cable length: 200mm
(Option : Cable comes from the side,from the end,from the bottom)
IP rating: IP67/IP68
Working Temperature:-40°C~+45°C
Fire rating:HB

Application: suit for indoor or outdoor light decoration
can be used in swimming pool

suit for class 2 power unit, maximum connected power not more than 100W



WP03AL2 (AP0502AL2) IP67/IP68 LED Linear Light





Part No.	Description	Picture	Part No.	Description	Picture
1.05.015.0051 (1m) 1.05.015.0052 (2m) 1.05.015.0053 (3.05m)	Aluminum profile		1.02.04.15.0019 (with hole) 1.02.04.15.0020 (w/o hole)	Frosted end cap	
1.16.005.0056 (1m) 1.16.005.0057 (2m) 1.16.005.0058 (3m)	PMMA one time extrusion profile		1.01.04.05.0013 1.01.05.0345 (M3*10)	End cap Self-tapping screws	
1.11.01.0079	EPOXY ADHESIVE				
1.05.015.0034 1m 1.05.015.0036 2m 1.05.015.0037 3m	Aluminum plate				

IP67/IP68 LED Profile
Dimension: W40.9*H44*L1000mm
(Customized length is available on request.)
Input voltage:24V DC
Power: 15W/meter
120pcs LED per meter
Color Temperature: 2400-6500K
CRI:≥80
(CRI more than 80 is available on request)
Beam Angle: 110°
Cable length: 200mm
(Option : Cable comes from the side,from the end,from the bottom)
IP rating: IP67/IP68
Working Temperature:-40°C~+45°C
Fire rating:HB

Application: suit for indoor or outdoor light decoration
can be used in swimming pool

suit for class 2 power unit, maximum connected power not more than 100W



WP03AL3 (AP0502AL3) IP67/IP68 LED Linear Light




Part No.	Description	Picture	Part No.	Description	Picture
1.05.015.0300 (1m) 1.05.015.0301 (2m) 1.05.015.0302 (3m)	Aluminum profile		1.02.04.15.0019 (with hole) 1.02.04.15.0020 (w/o hole)	Frosted end cap	
1.16.005.0056 (1m) 1.16.005.0057 (2m) 1.16.005.0058 (3m)	PMMA one time extrusion profile		1.05.015.0034 1m 1.05.015.0036 2m 1.05.015.0037 3m	Aluminum plate	
1.11.01.0079	EPOXY ADHESIVE		1.01.04.05.0016 1.01.05.0345 (M3*10)	End cap Self-tapping screws	

IP67/IP68 LED Profile
Dimension: W24.9*H34.2*L1000mm
(Customized length is available on request.)
Input voltage:24V DC
Power: 15W/meter
120pcs LED per meter
Color Temperature: 2400-6500K
CRI:≥80
(CRI more than 80 is available on request)
Beam Angle: 110°
Cable length: 200mm
(Option : Cable comes from the side,from the end,from the bottom)
IP rating: IP67/IP68
Working Temperature:-40℃~+45℃
Fire rating:HB

Application: suit for indoor or outdoor light decoration
can be used in swimming pool

suit for class 2 power unit, maximum connected power not more than 100W



WP04AL4 (AP0503AL4) IP67/IP68 LED Linear Light




Part No.	DescriPtion	Picture	Part No.	DescriPtion	Picture
1.05.005.0265 (1m) 1.05.005.0266 (2m) 1.05.005.0267 (3m)	Aluminum profile		1.05.005.0050 1m 1.05.005.0051 2m 1.05.005.0052 3m	Aluminum plate	
1.16.005.0045 (1m) 1.16.005.0046 (2m) 1.16.005.0047 (3m)	PMMA one time extrusion profile		1.11.01.0079	EPOXY ADHESIVE	
1.05.005.0190	Aluminum plate		1.02.04.05.0042 (with hole) 1.02.04.05.0043 (w/o hole)	Frosted end cap	

IP67/IP68 LED Profile
Dimension: W30.6*H30*L1000mm
(Customized length is available on request.)
Input voltage:24V DC
Power: 20W/meter
240pcs LED per meter
Color Temperature: 2400-6500K
CRI:≥80
(CRI more than 80 is available on request)
Beam Angle: 110°
Cable length: 200mm
(Option : Cable comes from the side,from the end,from the bottom)
IP rating: IP67/IP68
Working Temperature:-40°C~+45°C
Fire rating:HB

Application: suit for indoor or outdoor light decoration
can be used in swimming pool

suit for class 2 power unit, maximum connected power not more than 100W



WP04AL2 (AP0503AL2) IP67/IP68 LED Linear Light




Part No.	Description	Picture	Part No.	Description	Picture
1.05.005.0181 (1m) 1.05.005.0182 (2m) 1.05.005.0197 (3m)	Aluminum profile		1.05.005.0190	Aluminum plate	
1.16.005.0045 (1m) 1.16.005.0046 (2m) 1.16.005.0047 (3m)	PMMA one time extrusion profile		1.05.005.0050 1m 1.05.005.0051 2m 1.05.005.0052 3m	Aluminum plate	
1.01.04.05.0014	End cap		1.11.01.0079	EPOXY ADHESIVE	
1.01.05.0345 (M3*10)	Self-tapping screws				
1.02.04.05.0042 (with hole) 1.02.04.05.0043 (w/o hole)	Frosted end cap				

IP67/IP68 LED Profile
Dimension: W55.6*H63.7*L1000mm
(Customized length is available on request.)
Input voltage:24V DC
Power: 20W/meter
240pcs LED per meter
Color Temperature: 2400-6500K
CRI:≥80
(CRI more than 80 is available on request)
Beam Angle: 110°
Cable length: 200mm
(Option : Cable comes from the side,from the end,from the bottom)
IP rating: IP67/IP68
Working Temperature:-40°C~+45°C
Fire rating:HB

Application: suit for indoor or outdoor light decoration
can be used in swimming pool

suit for class 2 power unit, maximum connected power not more than 100W



WP04AL3 (AP0503AL3) IP67/IP68 LED Linear Light




Part No.	Description	Picture	Part No.	Description	Picture
1.05.005.0251 (1m) 1.05.005.0252 (2m) 1.05.005.0253 (3m)	Aluminum profile		1.05.005.0050 1m 1.05.005.0051 2m 1.05.005.0052 3m	Aluminum plate	
1.16.005.0045 (1m) 1.16.005.0046 (2m) 1.16.005.0047 (3m)			1.11.01.0079		
1.05.005.0195 (1m) 1.05.005.0194 (2m)			1.02.04.05.0042 (with hole) 1.02.04.05.0043 (w/o hole)		
1.01.04.05.0017	End cap				
1.01.05.0345 (M3*10)	Self-tapping screws				

IP67/IP68 LED Profile
Dimension: W30.6*H45*L1000mm
(Customized length is available on request.)
Input voltage:24V DC
Power: 20W/meter
240pcs LED per meter
Color Temperature: 2400-6500K
CRI:≥80
(CRI more than 80 is available on request)
Beam Angle: 110°
Cable length: 200mm
(Option : Cable comes from the side,from the end,from the bottom)
IP rating: IP67/IP68
Working Temperature:-40℃~+45℃
Fire rating:HB

Application: suit for indoor or outdoor light decoration
can be used in swimming pool

suit for class 2 power unit, maximum connected power not more than 100W



WP10AL2-NEW IP67/IP68 LED Linear Light




Part No.	Description	Picture	Part No.	Description	Picture
1.05.060.0022 (1M) 1.05.060.0021 (2M)	Aluminum profile		1.05.060.0030 (1M) 1.05.060.0031 (2M)	Aluminum plate	
1.16.060.0005 (3.2M)	PMMA one time extrusion profile		1.02.04.60.0006	Frosted end cap	
1.01.04.60.0002	End cap				
1.01.05.0345 (M3*10)	Self-tapping screws				

IP67/IP68 LED Profile
Dimension: W45*H45*L1000mm
(Customized length is available on request.)
Input voltage:24V DC
Power :30W/meter
240pcs LED per meter
Color Temperature: 2400-6500K
CRI:≥80
(CRI more than 80 is available on request)
Beam Angle: 120°
Cable length: 200mm
(Option : Cable comes from the end,from the bottom)
IP rating: IP67/IP68
Working Temperature:-40°C~+45°C
Fire rating:HB

Application: suit for indoor or outdoor light decoration
can be used in swimming pool

suit for class 2 power unit, maximum connected power not more than 100W



WP10AL1-NEW IP67/IP68 LED Linear Light




Part No.	Description	Picture	Part No.	Description	Picture
1.05.060.0017 (1M) 1.05.060.0018 (2M) 1.05.060.0019 (3.02M)	Aluminum profile		1.05.060.0030 (1M) 1.05.060.0031 (2M)	Aluminum plate	
1.16.060.0005 (3.2M)	PMMA one time extrusion profile		1.02.04.60.0006	Frosted end cap	
1.01.04.60.0001	End cap				
1.01.05.0345 (M3*10)	Self-tapping screws				


IP67/IP68 LED Profile
Dimension: W45*H80*L1000mm
(Customized length is available on request.)
Input voltage:24V DC
Power: 30W/meter
240pcs LED per meter
Color Temperature: 2400-6500K
CRI:≥80
(CRI more than 80 is available on request)
Beam Angle: 120°
Cable length: 200mm
(Option : Cable comes from the end,from the bottom)
IP rating: IP67/IP68
Working Temperature:-40°C~+45°C
Fire rating:HB

Application: suit for indoor or outdoor light decoration
can be used in swimming pool

suit for class 2 power unit, maximum connected power not more than 100W




FP01S IP67 Flexible LED Linear Light





Part No.	Description	Picture	Part No.	Description	Picture
1.16.025.0079 5M 1.16.025.0080 10M 1.16.025.0081 20M	silicone one time extrusion		1.01.07.0035 1.01.05.0030 (M3*16mm)	Metal Mounting clip Self-tapping screws	
1.05.025.0062 (1M)			1.01.07.0102 (1m) 1.01.07.0103 (5m) 1.01.07.0104 (10m)		
1.13.12.0132 (with hole) 1.13.12.0133 (w/o hole)	silicone End Cap		1.01.09.0030	steel strip	

IP67 Flexible LED Profile
Dimension: W10*H18.5*L1000mm
(Customized length is available on request.)
Input voltage:24V DC
120pcs LED per meter
Color Temperature: 2400-6500K
CRI:≥80
(CRI more than 80 is available on request)
Beam Angle: 110°
(Option : Cable comes from the end,from the bottom)
IP rating: IP67
Working Temperature:-40℃~+45℃
suit for 6-10mm width LED strip,
Maximum 10W/m
maximum 10meter length.
Application: suit for indoor or outdoor light decoration

suit for class 2 power unit, maximum connected power not more than 100W



Installation Wiring Diagram




Data				
Model	Dimension	Inch	Input Voltage	Max Power
FP01S-1000	1000(mm)	39.4(in)	24V	10W
FP01S-2000	2000(mm)	78.7(in)	24V	20W
FP01S-3000	3000(mm)	118.1(in)	24V	30W
FP01S-4000	4000(mm)	157.4(in)	24V	40W
FP01S-5000	5000(mm)	196.9(in)	24V	50W
FP01S-6000	6000(mm)	236.2(in)	24V	60W
FP01S-7000	7000(mm)	275.5(in)	24V	70W
FP01S-8000	8000(mm)	314.9(in)	24V	80W
FP01S-9000	9000(mm)	354.3(in)	24V	90W
FP01S-10000	10000(mm)	393.7(in)	24V	100W

Customized length is available on request.
LEDs we used are 3step,and CRI>80, CRI>90 is available by order.





FP07T IP67 Flexible LED Linear Light




Part No.	Description	Picture	Part No.	Description	Picture
1.16.025.0083	silicone one time extrusion		1.01.07.0124	Metal Mounting clip	
			1.01.05.0296 (M3*16)	Self-tapping screws	
1.05.025.0235 (1m) 1.05.025.0234 (2m) 1.05.025.0233 (3m)	Aluminum profile		1.02.04.25.0055 (with hole) 1.02.04.25.0054 (w/o hole)	silicone End Cap	
1.01.09.0030	steel strip				

IP67 Flexible Led linear light
suit for indoor or outdoor light decoration
linear light design , homogeneous and dots free
Installation: recessed or surface mounting
IP rating: IP67
Maximum 10W/m
suit for 6mm/8mm/10mm width LED strip,

suit for class 2 power unit, maximum connected power not more than 100W



Installation Wiring Diagram




Data				
Model	Dimension	Inch	Input Voltage	Max Power
FP07T-1000	1000(mm)	39.4(in)	24V	10W
FP07T-2000	2000(mm)	78.7(in)	24V	20W
FP07T-3000	3000(mm)	118.1(in)	24V	30W
FP07T-4000	4000(mm)	157.4(in)	24V	40W
FP07T-5000	5000(mm)	196.9(in)	24V	50W
FP07T-6000	6000(mm)	236.2(in)	24V	60W
FP07T-7000	7000(mm)	275.5(in)	24V	70W
FP07T-8000	8000(mm)	314.9(in)	24V	80W
FP07T-9000	9000(mm)	354.3(in)	24V	90W
FP07T-10000	10000(mm)	393.7(in)	24V	100W

Customized length is available on request.
LEDs we used are 3step,and CRI>80, CRI>90 is available by order.





FP07S IP67 Flexible LED Linear Light




Part No.	Description	Picture	Part No.	Description	Picture
1.16.025.0084	silicone one time extrusion		1.01.07.0124	Metal Mounting clip	
			1.01.05.0296 (M3*16)	Self-tapping screws	
1.05.025.0235 (1m) 1.05.025.0234 (2m) 1.05.025.0233 (3m)	Aluminum profile		1.02.04.25.0055 (with hole) 1.02.04.25.0054 (w/o hole)	silicone End Cap	

IP67 Flexible Led linear light
suit for indoor or outdoor light decoration
linear light design , homogeneous and dots free
Installation: recessed or surface mounting
IP rating: IP67
Maximum 10W/m
suit for 6mm/8mm/10mm width LED strip,

suit for class 2 power unit, maximum connected power not more than 100W



Installation Wiring Diagram



Data				
Model	Dimension	Inch	Input Voltage	Max Power
FP07S-1000	1000(mm)	39.4(in)	24V	10W
FP07S-2000	2000(mm)	78.7(in)	24V	20W
FP07S-3000	3000(mm)	118.1(in)	24V	30W
FP07S-4000	4000(mm)	157.4(in)	24V	40W
FP07S-5000	5000(mm)	196.9(in)	24V	50W
FP07S-6000	6000(mm)	236.2(in)	24V	60W
FP07S-7000	7000(mm)	275.5(in)	24V	70W
FP07S-8000	8000(mm)	314.9(in)	24V	80W
FP07S-9000	9000(mm)	354.3(in)	24V	90W
FP07S-10000	10000(mm)	393.7(in)	24V	100W

Customized length is available on request.
LEDs we used are 3step,and CRI>80, CRI>90 is available by order.

